DEFLEX FLEXIBLE CHANNELIZER DELINEATOR FOR WORK ZONES

ORANGE DEFLEX DELINEATOR CONSTRUCTION POST

Our **DEFLEX flexible channelizer delineator post for road work zones** is a popular tool to control traffic when space is at a premium in areas where construction occurs. It stands four (4) feet tall and is notably thin in profile. It is made of a treated polymer blend that is flexible when struck by vehicles and resistant to bad weather. The Deflex delineator is highly visible from all directions, day or night. It can be bolted in place or moved at will. Complies to T-RV-10 standards of the Ministère des Transports du Québec (MTQ).

PERFECT FOR NARROW ROAD WORK

GOOD STORAGE CAPACITY, 100 UNITS PER PICK-UP

VISIBLE AND FLEXIBLE 360°

1200 MM (8") HEIGHT WITH FOUR (4) REFLECTIVE STRIPES

EASY INSTALLATION ON MULTIPLE SURFACES

BEST VALUE ON THE MARKET

MADE OF FLEXIBLE POLYMER

FEATURES OF THE FLEXIBLE CHANNELIZER DELINEATOR FOR WORK ZONES

360° CHANNELIZER

Our delineator is visible and flexible from all angles.

MONOHULL

No mechanical pieces for easy maintenance. Less debris if damaged.

VERSATILE INSTALLATION

Can be installed permanently (bolted-in or glued), moved with a 7.25 kg (16 lb) weight base or anchoring system for an easy-in, easy-out installation.

UV-PROTECTED AND SOLID COLOR

A protective additive embedded in the polymer prevents color from fading.

THE DEFLEX flexible channelizer delineator post for road work zones IS MADE OF FLEXIBLE POLYMER AND REGAINS ITS ORIGINAL SHAPE AFTER MORE THAN 200 IMPACTS.

APPLICATIONS

Road Channelizing

Effective communication of road hazards is essential to improving safety and traffic flow. Road channelizing prevents accidents.

See the products

Work zone

Knowing that road workers are at risk every day, we develop tools that increase safety for road workers and drivers.

See the products

TECHNOLOGIES

Flexible delineator

Flexible road delineators that maximize safety for all road users, available in several colors.

Find out more

PRODUCT OPTIONS

- Rubber stabilizer 7.25kg / 16lb #33769
- Standard installation kit #35199
- Adhesive mastic for temporary installation #MA8C-DEFLEX
- LED cap with solar power #CAP3.5-LED

TECHNICAL SPECIFICATIONS OF DEFLEX FLEXIBLE CHANNELIZER DELINEATOR FOR WORK ZONES



DIMENSIONS

Height: 1220 mm (48")
Diameter: 90 mm (3.5")
Weight: 1.5 kg (3.3 lb)
Sheeting: 76 mm (3")

CERTIFICATIONS

MTQ T-RV-10
GUQ-1036

FEATURES

Proven product for over five (5) years in harsh weather conditions from -20 to +35°C (-4 to +95°F).

PERFORMANCE

360° of flexibility and visibility.
The Deflex delineator withstands 200 impacts at 70 kph (45 mph) and regains its original shape, even after being crushed by the wheels of heavy trucks.

MATERIALS

Delineator: Flexible Polymer with anti-UV
Sheeting: Diamond grade "prismatic", type IV

STANDARD

NCHRP-350

WEIGHT

1.5 kg (3.3 lb)

COMPOSITION

Molded-in and non-detachable flexible cap.
Four (4) embedded stripe sections protected from damage.
3M prismatic grade (type IV) reflective sheeting, flexible and visible on 360°.
Many colors available, pigment integrated into the polymer material.

Trafic innovation inc.
© 2022 All rights reserved.